

BẢNG GIÁ CONTACTOR MITSUBISHI + Role nhiệt (khởi động từ) 2013

Magnetic Contactor : Tiêu chuẩn IEC-60947-4-1 / EN60947-4-1/ VDE0660/ NEMA-ICS			
Loại		Điện áp cuộn Coil	Đơn giá 2013 (VNĐ)
S-N10		AC120(110-120V)/AC230V(220-240) / AC400V(380-415)	422,000
S-N12		AC120(110-120V)/AC230V(220-240) / AC400V(380-415)	506,000
S-N20		AC120(110-120V)/AC230V(220-240) / AC400V(380-415)	754,000
S-N25		AC120(110-120V)/AC230V(220-240) / AC400V(380-415)	1,001,000
S-N35		AC120(110-120V)/AC230V(220-240) / AC400V(380-415)	1,086,000
S-N50		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	2,165,000
S-N65		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	2,329,000
S-N80		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	3,328,000
S-N95		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	3,745,000
S-N125		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	5,239,000
S-N150		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	6,984,000
S-N180		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	8,729,000
S-N220		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	9,227,000
S-N300		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	15,127,000
S-N400		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	19,613,000
S-N600		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	48,941,000
S-N800		AC100(100-127V)/AC200V(200-240) / AC400V(380-440)	65,140,000
Mechanical Interlock (Khoá liên động cơ khí)			
UN-ML	11	Dùng cho S-N10/12	552,000
UN-ML	21	Dùng cho S-N20/25/35/50/65	689,000
UN-ML	80	Dùng cho S-N80/95/125	872,000
UN-ML	150	Dùng cho S-N150	933,000
UN-ML	220	Dùng cho S-N180/220/300/400	1,107,000
Auxiliary Contact Block (Khối tiếp điểm phụ)			
UN-AX11	1NO+1NC	Dùng cho S-N10/12/20/25/35/50/65	319,000
UN-AX2-1A1B	1NO+1NC	Dùng cho S-N10/12/20/25/35/50/65	339,000
UN-AX4-2A2B	2NO+2NC	Dùng cho S-N10/12/20/25/35/50/65	449,000
UN-AX80	1NO+1NC	Dùng cho S-N80/95/125	548,000
UN-AX150	1NO+1NC	Dùng cho S-N150/180/220/300/400	565,000
UN-AX2 2A	2NO	S-N10/12	435,000
UN-AX2 2B	2NC	S-N25/18/28	435,000
Relay contactor			
SR-N4		AC220V 2A2B	612,000
Time delay Module			
UN-TR4AN			1,242,000
Time delay relay			
SRT-NN AC220V 0~60sec (On delay)			2,638,000
Voltage detection relay			
SRE-KT (AC160~230V)			3,980,000
SRE-K (AC150~210V)			3,980,000
Thermal Overload Relay Tiêu chuẩn IEC-60947-4-1 / EN60947-4-1/ VDE0660/ NEMA-ICS			
Relay bảo vệ quá tải			
Loại		Dòng tác động bảo vệ	
TH-N 12		0.12, 0.17, 0.24, 0.35, 0.5, 0.7/0.9/1.3/1.7/2.1/2.5/3.6/5/6.6/9/11A	384,000
TH-N 20		0.24, 0.35, 0.5, 0.7, 0.9, 1.3, 1.7, 2.1, 2.5, 3.6/5/6.6/9/11/15/19A	431,000
TH-N 20TA		22/29/35A	476,000
TH-N 60		15/22/29/35/42/54A	667,000
TH-N 60TA		67/82/95A	729,000
TH-N 120		42/54/67/82A	1,034,000
TH-N 120TA		105/125A	1,155,000
TH-N 220RH		82/105/125/150/180/210A	2,514,000
TH-N 400RH		105/125/150/180/250/330A	2,955,000
TH-N 600		250/330/500/660A (*)	667,000
(*) CT khách hàng tự trang bị			
Relay bảo vệ quá tải có bảo vệ mất pha (phase fail protection thermal relay)			
TH-N 12 KP		0.12/ 0.17/ 0.24/0.35/ 0.5/ 0.7/0.9/1.3/1.7/2.1/2.5/3.6/5/6.6/9/11A	670,000
TH-N 20 KP		0.24/0.35/0.5/ 0.7/ 0.9/ 1.3/1.7/2.1/2.5/3.6/5/6.6/9/11/15/19A	735,000
TH-N 20TA KP		22/29/35A	774,000
TH-N 60 KP		15/22/29/35/42/54A	898,000

	TH-N 60TA KP		67/82/95A	1,155,000
	TH-N 120 KP		42/54/67/82A	2,037,000
	TH-N 120TA KP		105/125A	2,037,000
	TH-N 220RH KP		82/105/125/150/180/210A	4,168,000
	TH-N 400RH KP		105/125/150/180/250/330A	4,284,000
Relay điện tử bảo vệ quá tải, có bảo vệ mất pha (phase fail protection relay), thứ tự phase				
	ET-N60	1/4/8/20/60A	AC100V(100~120V)	6,424,000
	ET-N150	150A	AC100V(100~120V)	10,569,000
	ET-N360	360A	AC100V(100~120V)	12,424,000
	ET-N60	1/4/8/20/60A	AC200V(200~240V)	6,424,000
	ET-N150	150A	AC200V(200~240V)	10,569,000
	ET-N360	360A	AC200V(200~240V)	12,424,000
Contactơ điều khiển thuận nghịch, chốt tự giữ cơ khí				
	SL-2 x N21		AC200V(200-240V)/AC400V(380-440V)	7,423,000
	SL-2 x N35		AC200V(200-240V)/AC400V(380-440V)	9,312,000
	SL-2 x N50		AC200V(200-240V)/AC400V(380-440V)	12,999,000
	SL-2 x N65		AC200V(200-240V)/AC400V(380-440V)	13,175,000
	SL-2 x N80		AC200V(200-240V)/AC400V(380-440V)	24,237,000
	SL-2 x N95		AC200V(200-240V)/AC400V(380-440V)	24,325,000
	SL-2 x N125		AC200V(200-240V)/AC400V(380-440V)	34,421,000
	SL-2 x N150		AC200V(200-240V)/AC400V(380-440V)	34,857,000
	SL-2 x N220		AC200V(200-240V)/AC400V(380-440V)	45,657,000
	SL-2 x N300		AC200V(200-240V)/AC400V(380-440V)	54,173,000
	SL-2 x N400		AC200V(200-240V)/AC400V(380-440V)	58,386,000
	SL-2 x N600		AC200V(200-240V)/AC400V(380-440V)	228,264,000
	SL-2 x N800		AC200V(200-240V)/AC400V(380-440V)	244,065,000
Contactơ bán dẫn				
	US-N5SS		AC220V	4,132,000
	US-N8SS		AC220V	4,219,000
	US-N20		(AC220V)/(AC380V)	8,696,000
	US-N30		(AC220V)/(AC380V)	9,838,000
	US-N40		(AC220V)/(AC380V)	13,700,000
	US-N50		(AC220V)/(AC380V)	16,158,000