



CÔNG TY TRÁCH NHIỆM HỮU HẠN PHƯƠNG LAI

Trụ sở : 181/61/2 Phan Đăng Lưu - Phường 01, Quận Phú Nhuận

VPGD : 76 Đường 20 (Đường M3) KCN Tân Bình mở rộng, Q Bình Tân, TP HCM

Tel: (84-8)62705037 – Fax : 37658476 - MST : 0303750548

Email : phuonglaiplc@gmail.com – Website : <http://dien-congnghep.com>

BẢNG GIÁ BIẾN TẦN SIEMENS G110

Áp dụng từ 01/01/2012 - Giá chưa bao gồm thuế VAT

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
1	6SL3211-0AB12-5UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTER ₁ 1AC200-240V +10/-10% 47-63HZ ₁ ANALOG INPUT ₁ CT: 0.25KW; VT: 0.25KW ₁ CT-OVERLOAD: 150% 60S ₁ 150 X 90 X 116 (HXWXD) ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ WITHOUT BOP ₁ WITHOUT RS485-INTERFACE	123.92
2	6SL3211-0AB13-7UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTER ₁ 1AC200-240V +10/-10% 47-63HZ ₁ ANALOG INPUT ₁ CT: 0.37KW; VT: 0.37KW ₁ CT-OVERLOAD: 150% 60S ₁ 150 X 90 X 116 (HXWXD) ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ WITHOUT BOP ₁ WITHOUT RS485-INTERFACE	131.15
3	6SL3211-0AB15-5UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTER ₁ 1AC200-240V +10/-10% 47-63HZ ₁ ANALOG INPUT ₁ CT: 0.55KW; VT: 0.55KW ₁ CT-OVERLOAD: 150% 60S ₁ 150 X 90 X 131 (HXWXD) ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ WITHOUT BOP ₁ WITHOUT RS485-INTERFACE	144.57
4	6SL3211-0AB17-5UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTER ₁ 1AC200-240V +10/-10% 47-63HZ ₁ ANALOG INPUT ₁ CT: 0.75KW; VT: 0.75KW ₁ CT-OVERLOAD: 150% 60S ₁ 150 X 90 X 131 (HXWXD) ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +40 DEG C ₁ WITHOUT BOP ₁ WITHOUT RS485-INTERFACE	157.99

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
5	6SL3211-0AB21-1UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi ANALOG INPUTi CT: 1.1KW; VT: 1.1KW1 CT-OVERLOAD: 150% 60Si 160 X 140 X 142 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT RS485-INTERFACE	180.72
6	6SL3211-0AB21-5UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi ANALOG INPUTi CT: 1.5KW; VT: 1.5KW1 CT-OVERLOAD: 150% 60Si 160 X 140 X 142 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHOUT RS485-INTERFACE	205.50
7	6SL3211-0AB22-2UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi ANALOG INPUTi CT: 2.2KW; VT: 2.2KW1 CT-OVERLOAD: 150% 60Si 181 X 184 X 152 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT RS485-INTERFACE	244.73
8	6SL3211-0AB23-0UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi ANALOG INPUTi CT: 3.0KW; VT: 3.0KW1 CT-OVERLOAD: 150% 60Si 181 X 184 X 152 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHOUT RS485-INTERFACE	283.97
9	6SL3211-0AB12-5UB1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 0.25KW; VT: 0.25KW1 CT-OVERLOAD: 150% 60Si 150 X 90 X 116 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT ANA	123.92

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
10	6SL3211-0AB13-7UB1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 0.37KW; VT: 0.37KW CT-OVERLOAD: 150% 60Si 150 X 90 X 116 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT ANA	131.15
11	6SL3211-0AB17-5UB1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60Si 150 X 90 X 131 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHOUT ANA	157.99
12	6SL3211-0AB21-5UB1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 1.5KW; VT: 1.5KW CT-OVERLOAD: 150% 60Si 160 X 140 X 142 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHOUT ANAL	205.50
13	6SL3211-0AB22-2UB1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 2.2KW; VT: 2.2KW CT-OVERLOAD: 150% 60Si 181 X 184 X 152 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT ANAL	244.73
14	6SL3211-0AB12-5BB1	SINAMICS G110 - CPM110i AC-DRIVE,BUILT IN CL. B FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 0.25KW; VT: 0.25KW CT-OVERLOAD: 150% 60Si 150 X 90 X 116 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT ANA	139.40

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
15	6SL3211-0AB13-7BB1	SINAMICS G110 - CPM110i AC-DRIVE,BUILT IN CL. B FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 0.37KW; VT: 0.37KW CT-OVERLOAD: 150% 60Si 150 X 90 X 116 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHO	150.77
16	6SL3211-0AB13-7BB1	SINAMICS G110 - CPM110i AC-DRIVE,BUILT IN CL. B FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60Si 150 X 90 X 131 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHO	177.62
17	6SL3211-0AB21-5AB1	SINAMICS G110 - CPM110i AC-DRIVE,BUILT IN CL. A FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 1.5KW; VT: 1.5KW CT-OVERLOAD: 150% 60Si 160 X 140 X 142 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHOUT ANA	237.50
18	6SL3211-0AB22-2AB1	SINAMICS G110 - CPM110i AC-DRIVE,BUILT IN CL. A FILTERi 1AC200-240V +10/-10% 47-63HZi RS485-INTERFACE (USS-PROTOCOL)i CT: 2.2KW; VT: 2.2KW CT-OVERLOAD: 150% 60Si 181 X 184 X 152 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +50 DEG Ci WITHOUT BOPi WITHOUT ANA	280.88
19	6SL3211-0AB23-0UA1	SINAMICS G110 - CPM110i AC-DRIVE, WITHOUT FILTERi 1AC200-240V +10/-10% 47-63HZi ANALOG INPUTi CT: 3.0KW; VT: 3.0KW CT-OVERLOAD: 150% 60Si 181 X 184 X 152 (HXWXD)i PROTECTION IP20i AMBIENT TEMP -10 TO +40 DEG Ci WITHOUT BOPi WITHOUT RS485-INTERFACE	283.97
20	6SL3255-0AA00-4BA1	SINAMICS G110/G120i BASIC OPERATOR PANEL (BOP)	23.31