



CÔNG TY TRÁCH NHIỆM HỮU HẠN PHƯƠNG LAI

Trụ sở : 181/61/2 Phan Đăng Lưu - Phường 01, Quận Phú Nhuận

VPGD : 76 Đường 20 (Đường M3) KCN Tân Bình mở rộng, Q Bình Tân, TP HCM

Tel: (84-8)62705037 – Fax : 37658476 - MST : 0303750548

Email : phuonglaiplc@gmail.com – Website : <http://dien-congnghep.com>

BẢNG GIÁ BIẾN TẦN SIEMENS G120

Áp dụng từ 01/01/2012 - Giá chưa bao gồm thuế VAT

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
1	6SL3244-0BA20-1BA0	SINAMICS G120 ₁ CONTROL UNIT CU240S ₁ S-TYPE STANDARD ₁ RS485-INTERFACE, USS-PROTOCOL ₁ 9 DI, 3 DO, 2 AI, 2 AO ₁ PTC/KTY INTERFACE ₁ EM-BRAKE RELAY, MMC INTERFACE ₁ ENCODER INTERFACE ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ WITHOUT POWER MODULE AND BOP	207.61
2	6SL3244-0BA20-1PA0	SINAMICS G120 ₁ CONTROL UNIT CU240S DP ₁ S-TYPE STANDARD ₁ PROFIBUS DP ₁ 9 DI, 3 DO, 2 AI, 2 AO ₁ PTC/KTY INTERFACE ₁ EM-BRAKE RELAY, MMC INTERFACE ₁ ENCODER INTERFACE ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ WITHOUT POWER MODULE AND BOP	245.35
3	6SL3244-0BA20-1FA0	SINAMICS G120 ₁ CONTROL UNIT CU240S PN ₁ S-TYPE STANDARD ₁ PROFINET ₁ 9 DI, 4 DO, 2 AI, 2 AO ₁ PTC/KTY INTERFACE ₁ EM-BRAKE RELAY, MMC INTERFACE ₁ ENCODER INTERFACE ₁ PROTECTION IP20 ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ WITHOUT POWER MODULE AND BOP	275.55
4	6SL3244-0BA21-1PA0	SINAMICS G120 ₁ CONTROL UNIT CU240S DP-F ₁ S-TYPE SAFETY INTEGRATED ₁ PROFIBUS DP ₁ 8 DI, 3 DO, 2 AI, 2 AO ₁ PTC/KTY INTERFACE ₁ EM-BRAKE RELAY, MMC INTERFACE ₁ ENCODER INTERFACE ₁ PROTECTION IP20 ₁ AMBIENT TEMP 0 TO +45 DEG C ₁ WITHOUT POWER MODULE AND BOP	343.49

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
5	6SL3224-0BE13-7UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 0,37KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 173 X 73 X 145 (HXWXD), FSA ₁ PROTECTION IP20 ₁	183.24
6	6SL3224-0BE15-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 0,55KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 173 X 73 X 145 (HXWXD), FSA ₁ PROTECTION IP20 ₁	197.88
7	6SL3224-0BE17-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 0,75KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 173 X 73 X 145 (HXWXD), FSA ₁ PROTECTION IP20 ₁	212.55
8	6SL3224-0BE21-1UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 1,1KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 173 X 73 X 145 (HXWXD), FSA ₁ PROTECTION IP20 ₁	241.87
9	6SL3224-0BE21-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 1,5KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 173 X 73 X 145 (HXWXD), FSA ₁ PROTECTION IP20 ₁	285.84

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
10	6SL3224-0BE22-2UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 2,2KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 270 X 153 X 165 (HXWXD), FSB ₁ PROTECTION IP20 ₁	359.13
11	6SL3224-0BE23-0UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 3,0KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 270 X 153 X 165 (HXWXD), FSB ₁ PROTECTION IP20 ₁	432.42
12	6SL3224-0BE24-0UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 4,0KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 270 X 153 X 165 (HXWXD), FSB ₁ PROTECTION IP20 ₁	505.72
13	6SL3224-0BE25-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 5,5KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ OUTPUT LIGHT OVERLOAD: 7,5KW ₁ FOR 150% 3S,110% 57S,1	659.63
14	6SL3224-0BE27-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 7,5KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ OUTPUT LIGHT OVERLOAD: 11KW ₁ FOR 150% 3S,110% 57S,10	879.51

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
15	6SL3224-0BE31-1UA0	SINAMICS G120i POWER MODULE PM240i WITHOUT FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 11KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 15KW1 FOR 150% 3S,110% 57S,100	1,172.67
16	6SL3224-0BE31-5UA0	SINAMICS G120i POWER MODULE PM240i WITHOUT FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 15KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 18,5KW1 FOR 150% 3S,110% 57S,1	1,465.85
17	6SL3224-0BE31-8UA0	SINAMICS G120i POWER MODULE PM240i WITHOUT FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 18,5KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 22KW1 FOR 150% 3S,110% 57S,1	1,908.06
18	6SL3224-0BE32-2UA0	SINAMICS G120i POWER MODULE PM240i WITHOUT FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 22KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 30KW1 FOR 150% 3S,110% 57S,100	2,405.81
19	6SL3224-0BE33-0UA0	SINAMICS G120i POWER MODULE PM240i WITHOUT FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 30KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 37KW1 FOR 150% 3S,110% 57S,100	2,945.05

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
20	6SL3224-0BE33-7UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 37KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ OUTPUT LIGHT OVERLOAD: 45KW ₁ FOR 150% 3S,110% 57S,100	3,567.24
21	6SL3224-0BE34-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 45KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ OUTPUT LIGHT OVERLOAD: 55KW ₁ FOR 150% 3S,110% 57S,100	4,106.49
22	6SL3224-0BE35-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 55KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ OUTPUT LIGHT OVERLOAD: 75KW ₁ FOR 150% 3S,110% 57S,100	4,936.07
23	6SL3224-0BE37-5UA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITHOUT FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 75KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ OUTPUT LIGHT OVERLOAD: 90KW ₁ FOR 150% 3S,110% 57S,100	5,765.66
24	6SL3224-0BE22-2AA0	SINAMICS G120 ₁ POWER MODULE PM240 ₁ WITH BUILT IN CL. A FILTER ₁ WITH BULT IN BRAKING CHOPPER ₁ 3AC380-480V +10/-10% 47-63HZ ₁ OUTPUT HIGH OVERLOAD: 2,2KW ₁ FOR 200% 3S,150% 57S,100% 240S ₁ AMBIENT TEMP -10 TO +50 DEG C ₁ 270 X 153 X 165 (HXWXD), FSB ₁ PROTECTION	421.43

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
25	6SL3224-0BE23-0AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 3,0KW1 FOR 200% 3S,150% 57S,100% 240Si AMBIENT TEMP -10 TO +50 DEG Ci 270 X 153 X 165 (HXWXD), FSBi PROTECTION	505.72
26	6SL3224-0BE24-0AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 4,0KW1 FOR 200% 3S,150% 57S,100% 240Si AMBIENT TEMP -10 TO +50 DEG Ci 270 X 153 X 165 (HXWXD), FSBi PROTECTION	593.66
27	6SL3224-0BE25-5AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 5,5KW1 FOR 200% 3S,150% 57S,100% 240Si AMBIENT TEMP -10 TO +50 DEG Ci OUTPUT LIGHT OVERLOAD: 7,5KW1 FOR 150% 3	769.57
28	6SL3224-0BE27-5AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 7,5KW1 FOR 200% 3S,150% 57S,100% 240Si AMBIENT TEMP -10 TO +50 DEG Ci OUTPUT LIGHT OVERLOAD: 11KW1 FOR 150% 3S	1,026.10
29	6SL3224-0BE31-1AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 11KW1 FOR 200% 3S,150% 57S,100% 240Si AMBIENT TEMP -10 TO +50 DEG Ci OUTPUT LIGHT OVERLOAD: 15KW1 FOR 150% 3S,	1,319.26

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
30	6SL3224-0BE31-5AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 15KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 18,5KW1 FOR 150% 3	1,612.43
31	6SL3224-0BE31-8AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 18,5KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 22KW1 FOR 150% 3	2,115.46
32	6SL3224-0BE32-2AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 22KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 30KW1 FOR 150% 3S,	2,654.68
33	6SL3224-0BE33-0AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 30KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 37KW1 FOR 150% 3S,	3,256.14
34	6SL3224-0BE33-7AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 37KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 45KW1 FOR 150% 3S,	3,940.56

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
35	6SL3224-0BE34-5AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 45KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 55KW _i FOR 150% 3S,	4,521.28
36	6SL3224-0BE35-5AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 55KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 75KW _i FOR 150% 3S,	5,433.82
37	6SL3224-0BE37-5AA0	SINAMICS G120i POWER MODULE PM240i WITH BUILT IN CL. A FILTERi WITH BULT IN BRAKING CHOPPERi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 75KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 90KW _i FOR 150% 3S,	6,346.38
38	6SL3225-0BE25-5AA1	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 5,5KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 7,5KW _i FOR 150% 3S	1,044.42
39	6SL3225-0BE27-5AA1	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 7,5KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 11KW _i FOR 150% 3S,	1,319.26

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
40	6SL3225-0BE31-1AA1	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 11KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 15KW _i FOR 150% 3S,1	1,667.40
41	6SL3225-0BE31-5AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 15KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 18,5KW _i FOR 150% 3S	2,033.86
42	6SL3225-0BE31-8AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 18,5KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 22KW _i FOR 150% 3S	2,633.95
43	6SL3225-0BE32-2AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 22KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 30KW _i FOR 150% 3S,1	3,276.88
44	6SL3225-0BE33-0AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 30KW _i FOR 200% 3S,150% 57S,100% 240S _i AMBIENT TEMP -10 TO +50 DEG C _i OUTPUT LIGHT OVERLOAD: 37KW _i FOR 150% 3S,1	3,982.04

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
45	6SL3225-0BE33-7AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 37KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 45KW1 FOR 150% 3S,1	4,790.89
46	6SL3225-0BE34-5AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 45KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 55KW1 FOR 150% 3S,1	5,475.30
47	6SL3225-0BE35-5AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 55KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 75KW1 FOR 150% 3S,1	6,533.03
48	6SL3225-0BE37-5AA0	SINAMICS G120i POWER MODULE PM250i WITH BUILT IN CL. A FILTERi POSSIBILITY OF REGENERATIONi 3AC380-480V +10/-10% 47-63HZi OUTPUT HIGH OVERLOAD: 75KW1 FOR 200% 3S,150% 57S,100% 240S1 AMBIENT TEMP -10 TO +50 DEG C1 OUTPUT LIGHT OVERLOAD: 90KW1 FOR 150% 3S,1	7,570.02