



CÔNG TY TRÁCH NHIỆM HỮU HẠN PHƯƠNG LAI

Trụ sở : 181/61/2 Phan Đăng Lưu - Phường 01, Quận Phú Nhuận

VPGD : 76 Đường 20 (Đường M3) KCN Tân Bình mở rộng, Q Bình Tân, TP HCM

Tel: (84-8)62705037 – Fax : 37658476 - MST : 0303750548

Email : phuonglaipc@gmail.com – Website : <http://dien-congnghep.com>

BẢNG GIÁ BIẾN TẦN SIEMENS MICROMASTER 440

Áp dụng từ 01/01/2012 - Giá chưa bao gồm thuế VAT

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
1	6SE6440-2UD13-7AA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 0.37 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 0.37 KW ₁ 173 X 73 X 149 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	344.96
2	6SE6440-2UD15-5AA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 0.55 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 0.55 KW ₁ 173 X 73 X 149 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	359.77
3	6SE6440-2UD17-5AA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 0.75 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 0.75 KW ₁ 173 X 73 X 149 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	373.09
4	6SE6440-2UD21-1AA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 1.1 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 1.1 KW ₁ 173 X 73 X 149 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	396.77

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
5	6SE6440-2UD21-5AA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 1.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 1.5 KW ₁ 173 X 73 X 149 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	446.37
6	6SE6440-2UD22-2BA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 2.2 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 2.2 KW ₁ 202 X 149 X 172 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	516.69
7	6SE6440-2UD23-0BA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 3 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 3 KW ₁ 202 X 149 X 172 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	581.84
8	6SE6440-2UD24-0BA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 4 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 4 KW ₁ 202 X 149 X 172 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	654.38
9	6SE6440-2UD25-5CA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 5.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 7.5 KW ₁ 245 X 185 X 195 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	799.47

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
10	6SE6440-2UD27-5CA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 7.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 11 KW ₁ 245 X 185 X 195 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	984.53
11	6SE6440-2UD31-1CA1	MICROMASTER 440 ₁ WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 11 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 15 KW ₁ 245 X 185 X 195 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	1,265.84
12	6SE6440-2UD31-5DA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 15 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 18.5 KW ₁ 520 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	1,809.83
13	6SE6440-2UD31-8DA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 18.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 22 KW ₁ 520 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	2,077.96
14	6SE6440-2UD32-2DA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 22 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 30 KW ₁ 520 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	2,413.12
15	6SE6440-2UD33-0EA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 30 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 37 KW ₁ 650 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	3,100.19

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
16	6SE6440-2UD33-7EA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 37 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 45 KW ₁ 650 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	3,586.16
17	6SE6440-2UD34-5FA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 45 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 55 KW ₁ 850 X 350 X 320 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	4,139.16
18	6SE6440-2UD35-5FA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 55 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 75 KW ₁ 850 X 350 X 320 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	4,700.55
19	6SE6440-2UD37-5FA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 75 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 90 KW ₁ 850 X 350 X 320 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT AOP/BOP	5,538.44
20	6SE6440-2UD38-8FA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 90 KW ₁ OVERLOAD 136% 57 S, 160% 3 S ₁ SQUARED TORQUE POWER 110 KW ₁ 1400 X 326 X 356 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. 0 TO +40 DEG. C ₁ WITHOUT AOP/BOP	8,249.65
21	6SE6440-2UD41-1FA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 110 KW ₁ OVERLOAD 136% 57 S, 160% 3 S ₁ SQUARED TORQUE POWER 132 KW ₁ 1400 X 326 X 356 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. 0 TO +40 DEG. C ₁ WITHOUT AOP/BOP	9,535.72

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
22	6SE6440-2UD41-3GA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 132 KW ₁ OVERLOAD 136% 57 S, 160% 3 S ₁ SQUARED TORQUE POWER 160 KW ₁ 1533 X 326 X 545 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. 0 TO +40 DEG. C ₁ WITHOUT AOP/BOP	10,769.51
23	6SE6440-2UD41-6GA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 160 KW ₁ OVERLOAD 136% 57 S, 160% 3 S ₁ SQUARED TORQUE POWER 200 KW ₁ 1533 X 326 X 545 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. 0 TO +40 DEG. C ₁ WITHOUT AOP/BOP	12,128.77
24	6SE6440-2UD42-0GA1	MICROMASTER 440 WITHOUT FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 200 KW ₁ OVERLOAD 136% 57 S, 160% 3 S ₁ SQUARED TORQUE POWER 250 KW ₁ 1533 X 326 X 545 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. 0 TO +40 DEG. C ₁ WITHOUT AOP/BOP	14,115.38
25	6SE6440-2AD22-2BA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 2.2 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 2.2 KW ₁ 202 X 149 X 172 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHO	581.84
26	6SE6440-2AD23-0BA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 3 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 3 KW ₁ 202 X 149 X 172 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT A	652.90
27	6SE6440-2AD24-0BA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 4 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 4 KW ₁ 202 X 149 X 172 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT A	734.33

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
28	6SE6440-2AD25-5CA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 5.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 7.5 KW ₁ 245 X 185 X 195 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHO	903.12
29	6SE6440-2AD27-5CA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 7.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 11 KW ₁ 245 X 185 X 195 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOU	1,102.97
30	6SE6440-2AD31-1CA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 11 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 15 KW ₁ 245 X 185 X 195 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT	1,421.29
31	6SE6440-2AD31-8DA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 18.5 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 22 KW ₁ 520 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT	2,245.54
32	6SE6440-2AD33-0EA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 30 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 37 KW ₁ 650 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT A	3,351.55

NO STT	PART NUMBER MÃ SẢN PHẨM	DESCRIPTION MÔ TẢ ĐẶC TÍNH	LIST PRICE GIÁ (USD)
33	6SE6440-2AD33-7EA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 37 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 45 KW ₁ 650 X 275 X 245 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT A	3,871.05
34	6SE6440-2AD34-5FA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 45 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 55 KW ₁ 1150 X 350 X 320 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT	4,474.32
35	6SE6440-2AD35-5FA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 55 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 75 KW ₁ 1150 X 350 X 320 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT	5,077.60
36	6SE6440-2AD37-5FA1	MICROMASTER 440 ₁ WITH BUILT-IN CLASS A FILTER ₁ 3AC 380-480 V +10/-10% 47-63 HZ ₁ CONSTANT TORQUE POWER 75 KW ₁ OVERLOAD 150% 60 S, 200% 3 S ₁ SQUARED TORQUE POWER 90 KW ₁ 1150 X 350 X 320 (H X W X D) ₁ PROTECTION IP20 ₁ AMBIENT TEMP. -10 TO +50 DEG. C ₁ WITHOUT	5,982.52
37	6SE6400-0BP00-0AA0	MICROMASTER 4 ₁ BASIC OPERATOR PANEL (BOP)	32.77
38	6SE6400-0AP00-0AA1	MICROMASTER 4 ₁ ADVANCED OPERATOR PANEL (AOP)	127.39
39	6SE6400-0EN00-0AA0	MICROMASTER 4 ₁ ENCODER OPTION MODULE ₁ TTL DIFFERENTIAL ₁ / HTL INCREMENTAL ₁ 300 KHZ MAX., 5 V OR 24 V, 3W ₁ ENCA, ENCB, ENCZ // ENC-REC	142.16
40	6SE6400-0PM00-0AA0	MICROMASTER 4 BOP/AOP SINGLE ₁ INVERTER DOOR MOUNTING KIT	85.29
41	6SE6400-1PB00-0AA0	MICROMASTER 4 ₁ PROFIBUS MODULE	113.54